



air conditioning for every environment

January, 2006

**SUBMITTAL SCHEDULE  
cabinet unit heaters**

Name of job and location \_\_\_\_\_ Date \_\_\_\_\_  
 Architect \_\_\_\_\_ Engineer \_\_\_\_\_ Sheet \_\_\_\_\_ of \_\_\_\_\_  
 Contractor \_\_\_\_\_ Order No. \_\_\_\_\_  
 Submitted by \_\_\_\_\_

		Unit Tag			
Unit Quantity					
Model, Unit Size, and Air Flow Arrangement					
MBH Output					
CFM					
Entering Air Temperature °F					
Final Air Temperature °F					
Steam (PSI) or Entering Water Temp. °F					
Water Temperature Drop °F					
Water GPM					
Water Pressure Drop Ft. H <sub>2</sub> O					
<b>Factory Installed Options</b>		↓	↓	↓	↓
101	2-Row Coil, Hot Water Only				
110	Right Hand Piping				
112	Access Doors for Model WCC				
114	Front Panel Tamperproof Fasteners				
115	Key Locks on Access Doors				
116	Key Locks on Front Panel				
117	Aluminum Bar Grille - Inlet				
118	Aluminum Bar Grille - Outlet				
120	Decorator Color (specify from AIR75-402/AIR75-400)				
122	100% Air Inlet Duct Collar for Model WCC				
123	100% Air Outlet Duct Collar for Model WCC				
124	25% Outside Air Inlet Duct Collar for Model FC				
125	100% Outside Air Inlet Duct Collar for Model FC				
129	Leveling Bolts for Model FC				
134	25% Manual Outside Air Inlet Damper for Model FC				
135	100% Manual Outside Air Inlet Damper for Model FC				
136	100% Outside Air / 100% Inside Air Motorized Damper for Model FC				
137	25% Outside Air / 100% Inside Air Motorized Damper for Model FC				
138	Two Way Adjustable Louvers				
140	PSC Motor				
141	High Static Motor				
142	Plug-In Motor				
147	Disconnect Switch				
150	Unit Mounted Return Air Thermostat				

# AIR11-401.2

Field Installed Options	Unit Tag (continued from previous page)			
PermaLap® Frame to Recess Model WCC				
Wall Box for 25% Outside Air Dampers				
Extra Filter, Cleanable Aluminum				
Wall Gasket for Model FC				
Wall Gasket for Model WCC				
Thermostat, 9.8 amps @ 115V; 44°-86° F range, Honeywell T451A3005				
Thermostat, 16 amps @ 115V; 50°-80° range, Honeywell T4051A1003				
Thermostat, 10 amps @ 115V; 40°-90° F, auto-off-fan, Johnson T22BBC-1				
Thermostat Guard with Lock, Clear Plastic for all Thermostats Listed				
Aquastat, 10 amps @ 115V; 100°-240° F, Johnson A19DAC-1				
Manual Starter with TOL, off position, 1HP, 115V single phase, 1-pole				
2-Position Electric Valve for <b>sizes 2 thru 6</b> , 115V, 3/4" NPT, 15 PSI Max.				
2-Position Electric Valve for <b>sizes 8 thru 14</b> , 115V, 1" NPT, 15 PSI Max.				
3-Position Electric Valve for <b>sizes 2 thru 6</b> , 115V, 3/4" NPT, 15 PSI Max.				
3-Position Electric Valve for <b>sizes 8 thru 14</b> , 115V, 1" NPT, 15 PSI Max.				
Modulating non-Electric Valve, 48°-83° F range, for <b>sizes 2 thru 6</b> , 3/4" NPT				
Modulating non-Electric Valve, 48°-83° F range, for <b>sizes 8 thru 14</b> , 1" NPT				